

Datasheet

Finishmat® 6691



Lantor Finishmat® 6691

- Chemical and weather resistance
- Smooth surface
- Controlled resin drainage
- Prevention of fibre print through
- High abrasive resistance
- Easy to process due to high tensile strength
- Good resin retention
- Compatible with thermoset resins
- Excellent resin wet-out

Applications Lantor Finishmat® 6691

- Industrial: pipes, containers, tanks, profiles and rods
- General pultrusion and filament winding applications

| Properties | | 6691 SL | 6691 LL |
|--------------|-------------------|-----------|-----------|
| Thickness | mm | 0,30 | 0,45 |
| Roll length | m | 1000 | 1000 |
| Roll width | m | 1,0 | 1,0 |
| Dry weight | g/m ² | 20 | 40 |
| Resin uptake | kg/m ² | 0,35 | 0,50 |
| Binder | | Acrylate | Acrylate |
| Elongation | % | >10 | >10 |
| Fibre | type | Polyester | Polyester |

The information contained in this document has been compiled in good faith by Lantor BV, but nevertheless no representation or warranty is given as to the accuracy or completeness of the (technical) information provided herein. Lantor BV can not be held liable of any damages arising from any (printing) errors or omissions in this information. Lantor BV reserves the right to make changes with respect to the information provided at any time without further notice.

Information

Verlaat 22 - 3901 RG
Veenendaal - The Netherlands
t +31 (0)318 537 111
e composites@lantor.com

enabling performance

www.lantorcomposites.com

