

Composites

Datasheet

Finishmat® D77



Lantor Finishmat® D77

- Excellent surface finish
- Reduction of process cycle time
- Gelcoat can be replaced by pigmented resin
- Easy to process
- Becomes translucent in resin
- High elongation

Applications Lantor Finishmat® D77

- Marine: hulls, decks, and structures of boats and yachts
- Transportation: parts and panels of cars, trailers, trucks and RV's
- General closed mould applications

Properties		D77 60	D77 80
Thickness*	mm	0,30	0,40
Roll length	m	100	100
Roll width	m	Several widths	Several widths
Dry weight	g/m ²	60	80
Resin uptake*	kg/m ²	0,40	0,55
Binder		Needle punched	Needle punched
Elongation	%	100	100
Fibre	type	PAN	PAN

* Depending on process pressure

The information contained in this document has been compiled in good faith by Lantor BV, but nevertheless no representation or warranty is given as to the accuracy or completeness of the (technical) information provided herein. Lantor BV can not be held liable of any damages arising from any (printing) errors or omissions in this information. Lantor BV reserves the right to make changes with respect to the information provided at any time without further notice.

Information

Verlaat 22 - 3901 RG
Veenendaal - The Netherlands
t +31 (0)318 537 111
e composites@lantor.com

enabling performance

www.lantorcomposites.com

