

Lantor Skincore®

- Is a surface enhancement package for superior surface quality
- Is an easily drapeable and conformable material
- Is compatible with all regular types of resins, including Polyester, Vinylester, Phenolic and Epoxy
- Is suitable for infusion, CCBM and RTM Light

Applications Lantor Skincore®

- Transportation: deflectors, sideskirts, fenders, bonnets
- Marine: hulls, decks, hatches
- Construction: facadepanels, covers, shower trays, washbasins

Properties		A601
Thickness	mm	5
Thickness loss*	%	45
Roll length	m	40
Roll width	m	1,2
Max processing temp.	°C	170
Dry weight	g/m²	790
Glass weight	g/m²	600
Resin uptake*	kg/m²	2,1
Density impregnated*	kg/m³	875
Surface veil fibre	type	PAN

^{*} at -0,8 bar infusion

The information contained in this document has been compiled in good faith by Lantor BV, but nevertheless no representation or warranty is given as to the accuracy or completeness of the (technical) information provided herein. Lantor BV can not be held liable of any damages arising from any (printing) errors or omissions in this information. Lantor BV reserves the right to make changes with respect to the information provided at any time without further notice.

Information

Verlaat 22 - 3901 RG Veenendaal - The Netherlands

t +31 (0)318 537 111

e composites@lantor.com

enabling performance
www.lantorcomposites.com

